

WT800C Operations Manual Addendum

Congratulations on your purchase of our new WT800C integrated amplifier. If you're reading this, your unit is, in fact, a C version of our venerable WT800. There are a few differences between your unit and the WT800B, as follows:

Cosmetically, it's easy to tell a WT800C from earlier models. The C units feature our new back-lit logo. So, if the Eden logo lights up when you turn on your unit, you have a WT800C. That's easy, isn't it?

Mute to Tune – Pull the Input Gain knob (gently!) to mute all outputs except the Tuner Out. This allows silent tuning, a feature that guitarists and lead vocalists love.

DI Pre-/Post-EQ Select – You can now choose to send a Pre-EQ or Post-EQ signal through the DI output. The standard setting is Post-EQ. To send a Pre-EQ signal, pull the Enhance knob.

Those are the features you can see. However, we've also incorporated some cool safety features:

Mono Bridge Interlock Safety Circuit – When the amplifier is set to Bridge Mode operation, this circuit disconnects the Left and Right Outputs. This prevents accidental connection of the L/R outputs when in Bridge Mode. Only the Bridge Mono Output will work in Bridge Mode.

Amplifier Output Fuses – We've added internal fusing to both amplifiers. In the event of catastrophic failure, these fuses protect speaker cabinets from damage. It's not like this ever happened a lot, but on very rare occasions it has, and we wanted to give your speakers more protection. You're welcome.

Tuner Output – The output signal of the Tuner Out has been increased slightly. This will be helpful for those using tuners that need a very high output to operate properly.